

ACS Material LLC

Version: 1.2 / EN Revision Date: 5/08/2017

SECTION 1: IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1 Product identifiers

Product Name : ACS Material Graphene Dispersion in NMP

Brand : ACS Material LLC

CAS-No. : 7782-42-5 (graphene); 872-50-4 (NMP)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacturing of substances

1.3 Details of the supplier of the safety data sheet

Company : ACS MATERIAL LLC

959 E Walnut St. Suite 100 Pasadena, CA 91106

USA

Telephone : +1 (866)-227-0656 Fax : +1 (781)-518-0284

1.4 Emergency telephone number

Emergency Phone #: +1 (866)-227-0656

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Reproductive toxicity (Category 1B), H360

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

R61

Xi Irritant R36/37/38

For the full text of the R-phrases mentioned in this Section, see Section 16.





2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word

Danger

Hazard statement(s)

H227 Combustible liquid.
H315 Causes skin irritation.

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face

protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep

comfortable

for breathing. Call a POISON CENTER/doctor if you feel





ACS Material LLC

unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

IF exposed or concerned: Get medical advice/ attention. P308 + P313

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

Foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

Supplemental Hazard

Statements

None

Restricted to professional users.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 **Substances**

ACS Material Graphene Dispersion in NMP Substance name

CAS-No 7782-42-5 EC-No. 231-955-3

Synonyms Graphene, GNP Molecular weight 12.01 g/mol

Linear formula С

CAS-No 872-50-4





ACS Material LLC

EC-No. : 212-828-1

Synonyms: 1-Methyl-2-pyrrolidone

N-Methyl-2-pyrrolidone

NMP

 $M\text{-}\mathsf{PYROL}^{\mathsf{TM}}$

Molecular weight : 99.13 g/mol Linear formula : C_5H_9NO

Hazardous ingredients

Components	Concentration	CAS No.
Graphene (C)	~4 wt%	7782-42-5
NMP	94.9 wt%	872-50-4

For the full text of the phrases mentioned in this Section, see Section 16.

Hazardous impurities: None known.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed No data available.



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides, nitrogen oxides (NO_x).

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Suitable extinguishing media

Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge.



For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Store under inert gas. Moisture sensitive.

Storage class (TRGS 510): Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control	Basis
			Parameters	
Graphene	7782-42-5	TWA	15.000000Millio	USA. Occupational Exposure
(C)			n particles per	Limits (OSHA) - Table Z-3 Mineral
			cubic foot	Dusts
	Remarks	Millions of p	ons of particles per cubic foot of air, based on impinger bles counted by light-field techniques.	
		samples co		
		mppcf X 35	K 35.3 = million particles per cubic meter = particles per	
		C.C		
		Also see specific listing for Graphene (synthetic).		
		TWA	15.000000	USA. Occupational Exposure
			mg/m ³	Limits (OSHA) - Table Z-1 Limits
				for Air Contaminants
		TWA	5.000000	USA. Occupational Exposure
			mg/m ³	Limits (OSHA) - Table Z-1 Limits
				for Air Contaminants
		TWA	2.000000	USA. ACGIH Threshold Limit
			mg/m ³	Values (TLV)
		Pneumoconiosis		
N-methyl-2-	872-50-4	TWA	10.000000 ppm	USA. Workplace Environmental
pyrrolidone				Exposure Levels (WEEL)
	Remarks	Skin		
		PEL	1 ppm	California permissible exposure
			4 mg/m ³	limits for chemical contaminants
				(Title 8, Article 107)
		Skin		





Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
N-methyl-2- pyrrolidone	872-50-4	5-Hydroxy- Nmethyl-2- pyrrolidone	100.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

Derived No Effect Level (DNEL)

Application	Exposure	Health effect	Value
Area	routes		
Workers	Skin contact	Acute systemic effects	208mg/kg BW/d
Workers	Inhalation	Acute systemic effects	80 mg/m ³
Workers	Skin contact	Long-term systemic effects	19.8mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	40 mg/m ³

Predicted No Effect Concentration (PNEC)

· · · · · · · · · · · · · · · · · · ·	
Compartment	Value
Water	5 mg/l
Soil	0.138 mg/kg
Marine water	0.025 mg/kg
Fresh water	0.25 mg/l
Fresh water sediment	0.805 mg/kg
Onsite sewage treatment plant	10 mg/l

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

8.3 Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

The selected protective gloves must satisfy the specifications of EU Directive





ACS Material LLC

89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0,3 mm Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene Minimum layer thickness: 0,6 mm

Break through time: 30 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de.

test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Impervious clothing recommended. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

1) Appearance Form: liquid

Colour: colourless
2) Odour
No data available
3) Odour Threshold
No data available

4) pH 7,7 - 8



5) Melting point/freezing point -24 °C (-11.2 °F)

6) Initial boiling point and boiling range 202 °C

81 - 82 °C at 13 hPa
7) Flash point 91 °C - closed cup
8) Evaporation rate No data available

9) Flammability (solid, gas) No data available

10) Upper/lower flammability or explosive Upper explosion limit: 9,5 %(V) limits Upper explosion limit: 1,3 %(V)

11) Vapour pressure 0,39 - 0,43 hPa at 20 °C

1,32 hPa at 40 °C
12) Vapour density 3,42 - (Air = 1.0)
13) Relative density 1,028 g/mL at 25 °C
14) Water solubility No data available

15) Partition coefficient: n- octanol/water log Pow: -0,46
16) Auto-ignition temperature No data available
17) Decomposition temperature No data available

17) Decomposition temperatureNo data available18) Viscosity3000-5000 mPa·s

19) Explosive propertiesNo data available20) Oxidizing propertiesNo data available

9.2 Other safety information

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions, able to form peroxide composition in the air.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong acids, bases, strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon oxides and nitrogen oxides.

In the event of fire: see section 5.



ACS Material LLC



SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral

rat - 3.914 mg/kg Inhalation LC50

LC50 Inhalation: > 5130 mg/m³ (Rat 4 h)

Remarks: Lungs, Thorax, or Respiration: Other changes.

LDLO Inhalation rat - 4 h - > 5100 ppm

LD50 Dermal

rabbit - 8.000 mg/kg

Other information on acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Eyes - rabbit

Result: Eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Damage to fetus possible, occasional lethargy or irregular breathing.

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available





Aspiration hazard

No data available

Additional Information

RTECS: UY5790000

Prolonged or repeated exposure can cause: vomiting, diarrhea and/or abdominal pain. Rats exposed to 1-methyl-2-pyrrolidinone at a concentration of 1 mg/L as an aerosol for 10 days showed depletion of hematopoietic cells in the bone marrow and atrophy of the lymphoid tissues of the thymus, spleen, and lymph nodes.

Bone marrow - Irregularities - Based on Human Evidence

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - other fish - 4,000 mg/l - 96 h

LC50 - Leuciscus idus (Golden orfe) - > 500 mg/l - 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 - Daphnia magna (Water flea) - > 1,000 mg/l - 24 h

Toxicity to bacteria LC50 - Bacteria - > 9,000 mg/l

12.2 Persistence and degradability

Biodegradability Result: 90 % - Readily biodegradable

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.





Contaminated packaging

Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

UN number

ADR/RID: 1993 IMDG: - IATA: -

UN proper shipping name

ADR/RID: Combustible liquid, n.o.s. (N-methyl-2-pyrrolidone)

IMDG: Not dangerous goods IATA: Not dangerous goods

Transport hazard class(es)

ADR/RID: NONE IMDG: - IATA: -

Packaging group

ADR/RID: III IMDG: - IATA: -

Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

no data available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations and/or restrictions on use

N-methyl-2-pyrrolidone CAS-No.: 872-50-4

Candidate List of Substances of Very High Concern for Authorisation

Toxic for reproduction (article 57c)

ED/31/2011

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

N-methyl-2-pyrrolidone

CAS-No.

Revision Date



Safety Data Sheet – Graphene Dispersion	ersion in NMP	ACS Material LLC
	872-50-4	2007-07-01
SARA 311/312 Hazards		
Fire Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
N-methyl-2-pyrrolidone	CAS-No.	Revision Date
	872-50-4	2007-07-01
Pennsylvania Right To Know Components		
N-methyl-2-pyrrolidone	CAS-No.	Revision Date
	872-50-4	2007-07-01
New Jersey Right To Know Components		
N-methyl-2-pyrrolidone	CAS-No.	Revision Date
	872-50-4	2007-07-01

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation

Flam. Liq. Flammable liquids
H227 Combustible liquid.
H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation

H360 May damage fertility or the unborn child.

Repr. Reproductive toxicity

Skin Irrit. Skin irritation

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 2
Physical Hazard: 0

NFPA Rating

Health hazard: 2
Fire Hazard: 2
Reactivity Hazard: 0





ACS Material LLC

Disclaimer: ACS Material, LLC believes that the information in this Safety Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.

